

MATERIAL SAFETY DATA SHEET

REMINGTON ARMS COMPANY, INC.
870 REMINGTON DRIVE
MADISON, NC 27025-0700

DATE: April 19, 2010

Page 1 of 2

TELEPHONE NUMBERS:

Product Info - 910/548-8700 or 800/243-9700
Emergency - CHEMTREC 800/424-9300

HMIS RATING:

H - 1; F - 2; R - 0; PPE - N/A

NFPA RATING:

H - 0; F - 2; R - 0

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: **BriteBore** Bore Cleaner & Choke Tube Cleaner FORMULA NUMBER: #04064-1G
PRODUCT NUMBER: 2 OZ. - #18367 PRODUCT CLASS: CLEANER - LIQUID

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS#	% WT.	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE	
			TLV	PEL	MM	@EC
PETROLEUM DISTILLATE	8008-20-6	<55	200ppm	400ppm	0.2	20
MINERAL SEAL OIL	64742-06-9	<55	5ppm	5ppm	0.0	20

* - Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL DATA

BOILING RANGE: Not applicable.
EVAPORATION RATE: Slower than ether
LBS/GAL: N/A
FLASH POINT: 105°F (40.55°C) METHOD USED: CC

VAPOR DENSITY: Heavier Than Air
SOLUBILITY IN WATER: Negligible
SPECIFIC GRAVITY (H₂O=1): N/A

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Classification according to ASTM D-3065-77 and FHSA 1500.45 OSHA -
COMBUSTIBLE CLASS II LIQUID

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/D UPPER: N/D
EXTINGUISHING MEDIA: Use carbon dioxide, dry chemical, water fog, or foam.

USUAL FIRE AND EXPLOSION HAZARDS: Keep away from extreme heat or open flame. Vapor accumulation can flash or explode if ignited. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention.

SPECIAL FIREFIGHTING PROCEDURES: Water spray may be ineffective. Goggles and self-contained respiratory protection should be provided for firefighters fighting flames in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray (fog nozzles preferred).

SECTION V - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Inhalation X Ingestion X Dermal X

EFFECTS OF OVEREXPOSURE - SHORT-TERM:

- INHALATION - May cause irritation of respiratory tract, nausea, fatigue, dizziness, headache and depression of the central nervous system. Intentional misuse by deliberately concentrating and inhaling can be harmful or fatal.
- INGESTION - Not a likely route of exposure. May cause gastrointestinal irritation, nausea, vomiting and depression of the central nervous system.
- SKIN CONTACT - Contact may dry skin.; prolonged contact may cause moderate irritation.
- EYE CONTACT - Liquid or vapor can cause moderate to severe irritation.

EFFECTS OF OVEREXPOSURE - LONG TERM:

May cause moderate skin irritation from prolonged or repeated contact.

CARCINOGENICITY: NTP? No. IARC MONOGRAPHS? No. OSHA REGULATED? No.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY OVEREXPOSURE: None recognized.

(CONTINUED)

SECTION V - HEALTH HAZARD DATA (Cont'd)

EMERGENCY AND FIRST AID PROCEDURES:

- INHALATION - If user experiences breathing difficulty, remove to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.
- INGESTION - DO NOT induce vomiting. Call poison control center, hospital, emergency room or physician immediately.
- SKIN CONTACT - Wipe off with towel. Wash with soap and water.
- EYE CONTACT - Flush with large quantities of water for at least 15 minutes. Get medical attention.

SECTION VI - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Application to hot surfaces. Storage above 120EF. Exposure to open flame.

HAZARDOUS POLYMERIZATIONS: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce fumes when heated to decomposition. Fumes may contain carbon monoxide.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

SECTION VII - SPILL AND LEAK PROCEDURES

AQUATIC TOXICITY: 48 hour LC50, Pimephales promelas: >1,000 mg/L
 48 hour LC50, Daphnia pulex: 4.630 mg/L (Spearman)

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Avoid breathing vapors. Ventilate area. Remove source of ignition. Flush large spills of material into suitable retaining area or containers with large quantities of water. Small spills can be absorbed by appropriate inert absorbent and placed in closed containers for disposal.

WASTE DISPOSAL: Dispose in accordance with applicable local, state, and federal regulations.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store and use in cool, dry, well-ventilated areas. Do not store above 120EF or at elevated temperatures. Do not puncture or incinerate (burn) cans. Do not stick pin, nail, or any other sharp object into opening on top of can. Do not spray in eyes. Do not take internally. See product label for additional information.

OTHER PRECAUTIONS: Small pressurized containers of flammable products may be stored in areas suitable for ordinary combustibles with respect to construction, drainage, control of ignition sources, and ventilation, except that they should not be stored in basements. Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warning even after container is empty. Dispose of empty container according to local regulations.

SECTION IX - CONTROL MEASURES

RESPIRATORY PROTECTION: None under normal use. Avoid breathing vapors. For OSHA controlled work place, use only with adequate ventilation under engineered air control systems designed to provide maximum appropriate TLV. For occasional use where engineered air control is not feasible, use NIOSH approved respirators. For occasional consumer use, use only with adequate ventilation.

VENTILATION: Sufficient to prevent inhalation of solvent vapors. General dilution and/or local exhaust ventilation in volume or pattern to keep PEL/TLV of most hazardous ingredient below acceptable limit and LEL below stated limit.

PROTECTIVE GLOVES: None under normal use. Use of solvent resistant gloves required for prolonged or repeated contact.

EYE PROTECTION: None under normal use; however, use of safety glasses with splash guards or full face shields is recommended to safeguard against potential eye contact, irritation, or injury.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: None under normal use; however, use of solvent resistant aprons or other clothing is recommended.

WORK/HYGIENIC PRACTICES: Eye washes and safety showers in the workplace are recommended. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment which has been contaminated by prior use.

SECTION X - DISCLAIMER

NOTE: The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this information must be determined by the user to be in accordance with applicable federal, state, and local laws and regulations. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.