Remington Arms

Material Safety Data Sheet

This Material Safety Data Sheet has been prepared in compliance with Federal OSHA Hazard Communication Standard 29 CFR 1910.1200, ANSI Z400.1-1993 and the ISO Safety Data Sheet Standard. This product may be considered to be a hazardous chemical under 29 CFR 1910.1200. This information is required to be disclosed for safety in the workplace. *This MSDS is applicable only to the product identified herein and only when used properly.*

NOTE: Refer to Section XVII for List of Acronyms.

I. PRODUCT IDENTIFICATION

Product: COMPONENT EMPTY SHELLCASES (PRIMED) (ELECTRICALLY-INITIATED)

HMIS Rating
Health: 2
Flammability: 0
Reactivity: 1

IN EVENT OF EMERGENCY
(Spill, Leak, Fire, Exposure, Accident)
CALL CHEMTREC DAY OR NIGHT
(800) 424-9300
In Washington, D.C. 483-7616
Outside Continental U.S.A. (202) 483-7616

II. HAZARDOUS COMPONENT INFORMATION

Component Electrically-Initiated Empty Shellcase (Primed) is comprised of the following two (2) components. The hazardous chemicals contained in each are listed. The percent by weight of the hazardous ingredients in Centerfire/Rimfire Ammunition are listed in the table below.

1. Brass Shellcase Copper, Zinc, Nickel

2. Primer Copper, Zinc, Antimony, Barium, Lead Styphnate, Aluminum

Hazardous Ingredients	Percent by Weight	CAS Number	Exposure Limits (PEL)
Copper	68-70%	7440-50-8	None established
Zinc	29-30%	7440-66-6	TWA (fume) 0.1 mg/m ³
			TWA (dust, mist) 1.0 mg/m ³
Nickel	Less than 1%	7440-02-0	TWA Soluble Compounds:
			0.1 mg/m^3
			TWA Insoluble Compounds
			1.0 mg/m^3
Antimony	Less than 0.1%	7440-36-0	TWA 0.5 mg/m ³
Barium	Less than 0.3%	7440-39-3	TWA 0.5 mg/m ³
Lead Styphnate	Less than 0.3%	63918-97-8	None established
Lead Trinitroresorcinate			
Aluminum	Less than 0.1%	7429-90-5	TWA 15 mg/m ³

Revised: October, 2001 Page 1 of 6

Issued: March, 1996

III. HAZARDS IDENTIFICATION

Emergency Overview: Accidental fire may cause low-energy fragments to be emitted thus

causing potential eye injury.

Potential Human Health Effects:

Skin Contact: May cause allergic reaction (sensitization) in susceptible individuals.

Eye Contact: Dust and fumes can irritate the eyes causing redness and discharge.

Inhalation: Inhalation of dust or fumes may cause irritation to nose, throat, upper

respiratory tract and lungs. Irritation may lead to bronchitis, headache,

lowering of blood pressure and weakness.

Ingestion/Absorption: Ingestion may cause severe headache, nausea, vomiting, abdominal

pain, fatigue, diarrhea, trembling, ringing in ear and salivation.

Carcinogenicity Information: This product is not classified a carcinogen by IARC, OSHA, NTP or

EPA. Lead is classified a carcinogen by IARC.

IV. FIRST AID MEASURES

Skin Contact: Wash affected area thoroughly with soap and water. Remove contaminated

clothing. Wash clothing thoroughly prior to reuse. Discard any contaminated

leather items (i.e. shoes, etc.).

Eye Contact: If wearing contacts, immediately remove contact lenses. Hold eyelids apart and

flush eyes thoroughly with water for at least 15 minutes. Obtain medical

attention immediately.

Inhalation: Immediately remove to fresh air. Administer artificial respiration, if necessary.

If breathing is difficult, administer oxygen. Obtain medical attention

immediately.

Ingestion/Absorption: If conscious, drink large amounts of water. Induce vomiting. Immediately

contact a physician or Poison Control Center. *Never* induce vomiting or give

anything by mouth to an unconscious person.

V. FIRE HAZARDS

Flammable Properties: May ignite if heated to 250°F. Will ignite when exposed to flame and high

temperatures. Be cautious of low-energy fragments.

Extinguishing Media: Flood fire with water to fight fire and cool shells. If no water is available,

use carbon dioxide, dry chemical or earth.

Fire-Fighting Instructions: Evacuate area immediately. Deluge area with water. Wear full fire-

fighting protective gear including face shield or SCBA to protect from

fragments.

Revised: October, 2001 Page 2 of 6 Issued: March, 1996

VI. ACCIDENTAL RELEASE MEASURES

Safeguards: Remove from all sources of ignition.

Spill Cleanup: Use non-sparking equipment to clean up spill. If disposal is necessary, refer

to XIII. DISPOSAL CONSIDERATIONS.

Accidental Release: See above.

VII. HANDLING AND STORAGE

Personnel Handling: Handle with care. Do not strike or crush the components. Always wash

hands thoroughly after handling.

Storage: Store in original containers in a cool, dry, well-ventilated area away from all

sources of ignition. Do not subject to mechanical shock. Keep out of reach of children. This product *must not be stored* with acids, strong oxidizers or

caustics.

VIII. PERSONAL PROTECTION/EXPOSURE CONTROLS

Engineering Controls: Local exhaust ventilation is recommended if significant dusting occurs.

Otherwise, use general exhaust ventilation.

Personal Protective Equipment: Safety glasses recommended when handling or firing rounds.

Hearing protection recommended when firing rounds.

Use of a NIOSH/MSHA-approved respirator is recommended when concentrations to fumes and/or dust exceed the PEL or TLV.

Exposure Guidelines: Keep product away from sources of accidental ignition.

Exposure Limits: Exposure limits listed with each hazardous chemical.

IX. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL DATA

Form: Solid Evaporation Rate: N/A

Color: Variable Melting Point: 100°C-400°C

Odor: None Solubility in Water: N/A
Boiling Point: N/A pH: N/A

Specific Gravity:N/AVapor Pressure:N/AVapor Density:N/A

Revised: October, 2001 Page 3 of 6 Issued: March, 1996

X. STABILITY AND REACTIVITY

Chemical Stability: Stable under normal use conditions. Will not react with water.

Other Hazards:

Incompatibility: Incompatible with acids, strong oxidizers and caustics.

Polymerization: Will not occur.

Conditions to Avoid: Flames, sparks, percussion, shock, static, high temperatures (266°F or 130°C, or

above)

XI. TOXICOLOGICAL INFORMATION

Oral LD 50: No available data.

Dermal LD 50: No available data.

Inhalation LC 50: No available data.

Irritation: No available data.

Not a skin or eye irritant.

XII. ECOLOGICAL INFORMATION

Aquatic Toxicity:

Lead (LC 50) to Bluegill: 2-5 mg/l Barium to Stickleback: 400 mg/l Barium Nitrate to Stickleback: 760 mg/l

Environmental Impact:

When used and disposed of properly, there is no known environmental impact.

XIII. DISPOSAL CONSIDERATIONS

This product is considered a characteristic hazardous waste per 40 CFR 261.24 *for disposal purposes only*. Dispose of as required by local, state and federal laws and regulations.

EPA Hazardous Waste Code: D008 (lead)

XIV. TRANSPORTATION INFORMATION

SHIPPING INFORMATION

Proper Shipping Name: Cases, Cartridge, Empty with Primer

Hazard Class: N/A UN/NA No: N/A Packing Group: N/A

Shipping Label: None required.

Special Information: May be reclassified internationally as:

Hazard Class: 1.4S UN/NA No.: UN0055 Packing Group: II Shipping Label: 1.4S label

Revised: October, 2001 Page 4 of 6

Issued: March, 1996

XV. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA Inventory Status: Included on list.

This product contains a toxic chemical or chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

XVI. OTHER INFORMATION

NFPA Rating: Not established.

HAZARD CLASSIFICATION

Chronic Health: Headache, nausea, weakness
Acute Health: Anemia, embryotoxin.

Fire Hazard: 0 (per HMIS Rating)

Pressure Hazard: Sudden release of pressure.

Reactivity Hazard: 1 (per HMIS Rating)

NPCA-HMIS Ratings:

Health: 2 Flammability: 0 Reactivity: 1

References:

Code of Federal Regulations, Monthly Summary, CFR 1910.1200(g) and Appendix E (B.), Regulations Management Corporation, Bloomington, Indiana, July 1, 1994.

Hazardous Chemical Desk Reference: Third Edition, Richard J. Lewis, Sr., Van Nostrand Reinhold, Copyright 1993.

American National Standards Institute, Z400.1-1993.

International Standards Organization Safety Data Sheet Standard.

Revised: October, 2001 Page 5 of 6 Issued: March, 1996

XVII. LIST OF ACRONYMS

ACGIH American Conference of Governmental Industrial Hygienists

AIHA WEEL American Industrial Hygiene Association-Workplace Environmental Exposure Level

ANSI American National Standard Institute

BEI Biological Exposure Indexes
CAS Chemical Abstract Service
CFR Code of Federal Regulations
CL Ceiling Limits (not to be exceeded)

DSL Domestic Substances List

EPA Environmental Protection Agency

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer
IATA International Air Transport Association
ICAO International Civil Aviation Organization
ISO International Standards Organization

LC Lethal Concentration

LD Lethal Dose

MITI Ministry of International Trade and Industry (Japan)

MSHA Mine Safety and Health Appliance
NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety and Health

NTA National Transportation Agency (Canada)

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

ORM Other Regulated Materials

PEL Permissible Exposure Limit (OSHA)
SCBA Self-contained Breathing Apparatus

STELShort-Term Exposure LimitTLVThreshold Limit Values (ACGIH)TSCAToxic Substances Control ActTWATime Weighted Average

UN/NA United Nations/North American (Identification number)
SARA Superfund Amendments and Reauthorization Act
RCRA Resource Conservation and Recovery Act

For additional information, please contact:

Remington Arms Company, Inc. P.O. Box 700 870 Remington Road Madison, NC 27025-0700

(800) 243-9700

The information contained in this *Material Safety Data Sheet* is provided to all individuals who are or will be exposed to this product through use, handling, storage or transport. Remington believes, yet makes no warranty, that all information contained in this document is current as of the date of publication.

Revised: October, 2001 Page 6 of 6 Issued: March, 1996